




# PDC BITS

# 12 1/4" KDC569SU

## DESIGN FEATURES:

- 3D designed 4140 alloy steel body CNC machined for maximum blade and body strength.
- Tungsten Carbide hardfacing in critical areas for increased erosion and abrasion resistance.
- TCI enhanced gage pads for increased protection.
- Optimized parabolic profile for blade count, cutter quantity and bit stability.
- Force-Balanced PDC cutter locations minimize bit whirl and drill a precise round hole.
- Asymmetric blade design reduces drilling harmonics.

Body Type .....Two-piece 4140 Alloy Steel  
 Gage Length .....2.50 in.  
 Overall Length .....19.56 in.  
 Shipping Weight .....TBD  
 Pin Connection .....6-5/8" API Regular  
 Fishneck Diameter .....8.00 in.  
 Fishneck Length .....5.60 in.  
 Make-Up Length .....14.62 in.  
 Make-Up Torque .....38,000 to 41,800 ft/lbs  
 Face Cutters .....55 @ 16mm PDC  
 Back-Up Cutters .....n/a  
 Gage Cutters .....6 @ 13mm PDC  
 Up-Drill Cutters .....6 @ 13mm PDC  
 Nozzle Type .....9 @ LOP Nozzle  
 TFA (min – max) .....0.69 in<sup>2</sup> to 2.76 in<sup>2</sup>  
 Weight on Bit (WOB) .....5,000 to 25,000 lbs.  
 Rotary Speed (RPM) .....60 to 250 RPM



[www.kazduco.com](http://www.kazduco.com)  
 Member of the FSU investment group

### OFFICE IN THE NETHERLANDS

Laan 1933 # 37, 6711 NX EDE  
 Phone: +31 (318) 504499  
 Fax: +31 (318) 614752

### OFFICE IN KAZAKHSTAN:

Office 304, Kurmangazy St. 48a  
 Almaty, Kazakhstan  
 Tel./fax: +7 (727) 261 38 58  
 E-mail: [bits@kazduco.com](mailto:bits@kazduco.com)